





Australian Lighting Solutions

COB LED spotlight

Picture	Specification	Beam angle	CCT(K) (Epistar COB LED)	Product Dimension
		90°	2600k-3700K, 450Lm	
	BASE: GU10/E27			
	INPUT: AC100-240V		5100-7000k, 550 Lm	
	POWER: 5W			
	Weight: 60g			
	Ambient temperature: 20-40℃			
DL-LS5W-HV	CRI:70Ra			
		90°	2600k-3700K, 450Lm	
	BASE: GU5.3			
	INPUT: AC12V/24V		5100-7000k, 550 Lm	
	POWER: 5W			
	Weight: 60g			
	Ambient temperature: 20-40℃			
DL-LS5W-LV	CRI:70Ra			
		90°	2600k-3700K, 700Lm	
	BASE: GU10/E27			
	INPUT: AC100-240V		5100-7000k, 900 Lm	
	POWER: 8W			
	Weight: 100g			
	Ambient temperature: 20-40℃			
DL-LS8W-HV	CRI:70Ra			
		90°	2600k-3700K, 700Lm	
	BASE: GU5.3			
	INPUT: AC12V/24V		5100-7000k, 900 Lm	
	POWER: 8W			
	Weight: 100g			
	Ambient temperature: 20-40℃			
DL-LS8W-LV	CRI:70Ra			







COB LED spotlight

Picture	Specification	Beam angle	CCT(K) (Sharp LED)	CCT(K) (Everlight LED)	Product Dimension
		24°/38°/60°			
	BASE: GU10/E27				
	INPUT: AC100-240V		2500-3700k, 340Lm	2500-3700k, 320Lm	
	POWER: 6W				
	Weight: 60g		3800K-5000K, 360 Lm	3700K-5000K, 340 Lm	
	Ambient temperature: 20-40℃				
DL-LS6W-HV	CRI:>80Ra		5100k-7000K, 420 Lm	5100k-7000K, 400 Lm	Φ49.5*H80.5mm

Australian Lighting Solutions Pty. Ltd.

4 Tampe Road. Rowville. Victoria. 3178. Australia www.australianlightingsolutions.com.au


Australian Lighting Solutions

	BASE: GU5.3	24°/38°/60°	2500-3700k, 340Lm	2500-3700k, 320Lm	
	INPUT: AC12V/24V				
	POWER: 6W		3800K-5000K, 360 Lm	3800K-5000K, 340 Lm	
	Weight: 60g				
	Ambient temperature: 20-40°C				
DL-LS6W-LV	CRI:>80Ra		5100k-7000K, 420 Lm	5100k-7000K, 400 Lm	Φ49.5*H64mm
	BASE: GU10/E27	24°/38°/60°	2500-3700k, 560Lm	2500-3700k, 540Lm	
	INPUT: AC100-240V				
	POWER: 10W		3800K-5000K, 580 Lm	3800K-5000K, 560 Lm	
	Weight: 122g				
	Ambient temperature: 20-40°C				
DL-LS10W-HV	CRI:>80Ra		5100k-10000K, 620 Lm	5100k-10000K, 600 Lm	Φ50*H116mm
	BASE: GU5.3	24°/38°/60°	2500-3700k, 560Lm	2500-3700k, 540Lm	
	INPUT: AC12V/24V				
	POWER: 10W		3800K-5000K, 580 Lm	3800K-5000K, 560 Lm	
	Weight: 122g				
	Ambient temperature: 20-40°C				
DL-LS10W-LV	CRI:>80Ra		5100k-10000K, 620 Lm	5100k-10000K, 600 Lm	Φ50*H106mm
	BASE: GU10/E27	20°/30°/40°	2600k-3700K, 270Lm	2600k-3700K, 250Lm	
	INPUT: AC100-240V				
	POWER: 5W		3800K-5000K, 300 Lm	3800K-5000K, 280 Lm	
	Weight: 60g				
	Ambient temperature: 20-40°C				
DL-LS5W-HV	CRI:>80Ra		5100-7000k, 330 Lm	5100-7000k, 310 Lm	Φ50*H64mm
	BASE: GU5.3	20°/30°/40°	2600k-3700K, 270Lm	2600k-3700K, 250Lm	
	INPUT: AC12V/24V				
	POWER: 5W		3800K-5000K, 310 Lm	3800K-5000K, 280 Lm	
	Weight: 60g				
	Ambient temperature: 20-40°C				
DL-LS5W-LV	CRI:>80Ra		5100-7000k, 330 Lm	5100-7000k, 310 Lm	Φ50*H56mm
	BASE: GU10/E27	20°/30°/40°	2600k-3700K, 400Lm	2600k-3700K, 380Lm	
	INPUT: AC100-240V				
	POWER: 8W		3800K-5000K, 440 Lm	3800K-5000K, 420 Lm	
	Weight: 100g				
	Ambient temperature: 20-40°C				
DL-LS8W-HV	CRI:>80Ra		5100-7000k, 470 Lm	5100-7000k, 450 Lm	Φ50*H91mm



Australian Lighting Solutions Pty. Ltd.

4 Tampe Road. Rowville. Victoria. 3178. Australia www.australianlightingsolutions.com.au


Australian Lighting Solutions

	BASE: GU5.3	20°/30°/40°	2600k-3700K, 400Lm	2600k-3700K, 380Lm	
	INPUT: AC12V/24V				
	POWER: 8W				
	Weight: 100g		3800K-5000K, 440 Lm	3800K-5000K, 420 Lm	
	Ambient temperature: 20-40°C				
DL-LS8W-LV	CRI:>80Ra		5100-7000k, 470 Lm	5100-7000k, 450 Lm	Φ50*H83mm

COB LED spotlight

Picture	Specification	Beam angle	CCT(K) (CREE LED)	Product Dimension
	BASE: GU10/E27	24°/38°/60°	2500-3700k, 700Lm	
	INPUT: AC100-240V			
	POWER: 10W		3800K-5000K, 750 Lm	
	Weight: 122g			
	Ambient temperature: 20-40°C			
DL-LS10W-HV	CRI:>80Ra		5100k-10000K, 800 Lm	Φ50*H116mm
	BASE: GU5.3	24°/38°/60°	2500-3700k, 700Lm	
	INPUT: AC12V/24V			
	POWER: 10W		3800K-5000K, 750 Lm	
	Weight: 122g			
	Ambient temperature: 20-40°C			
DL-LS10W-LV	CRI:>80Ra		5100k-10000K, 800 Lm	Φ50*H106mm

SMD LED spotlight


Picture	Specification	Beam angle	CCT(K) (Samsung SMD5630 LED)	Product Dimension
	BASE: GU10/E27	60°	2600k-3700K, 450Lm	
	INPUT: AC100-240V			
	POWER: 5W		3800K-5000K, 480 Lm	
	Weight: 60g			
	Ambient temperature: 20-40°C			
DL-LS5W-HV	CRI:>80Ra		5100-7000k, 500 Lm	Φ50*H61mm
	BASE: GU5.3	60°	2600k-3700K, 450Lm	
	INPUT: AC12V/24V			
	POWER: 5W		3800K-5000K, 480 Lm	
	Weight: 60g			
	Ambient temperature: 20-40°C			
DL-LS5W-LV	CRI:>80Ra		5100-7000k, 500 Lm	Φ50*H51mm

Australian Lighting Solutions Pty. Ltd.


4 Tampe Road. Rowville. Victoria. 3178. Australia www.australianlightingsolutions.com.au

Australian Lighting Solutions

SMD LED PAR38 LAMP

Picture	Specification	Beam angle	CCT(K) (Samsung SMD 5630 LED)	Product Dimension
	LED qty: 48pcs SMD5630	120°	2500k-3700k, 1400Lm	
	BASE: E26/E27			
	INPUT: AC100-240V		3800-5000K, 1500 Lm	
	POWER: 24W			
	Weight: 430g		5000-7000k, 1650 Lm	
	Ambient temperature: 20-40℃			
DL-PAR38-HV	CRI:>80Ra		Φ122*H120.5mm	

COB PAR30/PAR38/AR111 LED LAMP

Picture	Specification	Beam angle	CCT(K) (Sharp LED)	Product Dimension
 GU10	BASE: E27/G53/GU10	24°/38°/60°	Warm white 3000k, 650Lm	
	INPUT: AC100-240V			
	POWER: 15W			
	Weight: 360g		Neutral white 3800-5000K, 720 Lm	
	Ambient temperature: 20-40℃			
	CRI:>80Ra			
DL-AR111-HV			Φ111*H69mm	
	BASE: E26/E27	24°/38°/60°	Warm white 3000k, 650Lm	
	INPUT: AC100-240V			
	POWER: 15W			
	Weight: 360g		Neutral white 3800-5000K, 720 Lm	
	Ambient temperature: 20-40℃			
	CRI:>80Ra			
DL-PAR30-HV			Φ94.95*H98mm	
	BASE: E26/E27	24°/38°/60°	Warm white 3000k, 1100Lm	
	INPUT: AC100-240V			
	POWER: 22W			
	Weight: 430g		Neutral white 4000K, 1180 Lm	
	Ambient temperature: 20-40℃			
	CRI:>80Ra			
DL-PAR38-HV			Φ122*H125mm	

Australian Lighting Solutions Pty. Ltd.

4 Tampe Road. Rowville. Victoria. 3178. Australia www.australianlightingsolutions.com.au