

Australian Lighting Solutions

LED tunnel light			
Picture	Specification	Beam angle	CCT(K) (CREE XTE LED)
	Power consupction: 30Watt	IP65	2500k-3700k,2500 Lm
	LED type: high power	LED chip: 24pcs CREE XTE	
	Power efficiency: >85%	Lumens efficiency: 100Lm	3800-5000K, 2900 Lm
	Beam angle: 100°120°/150°85°/155°80°	Material: Aluminum	
	Input voltage: AC100-240V (HLG-60W)		5000-7000k, 3200 Lm
30w tunnel			
	Power consupction: 60Watt	IP65	2500k-3700k,5000 Lm
	LED type: high power	LED chip: 48pcs CREE XTE	
	Power efficiency: >85%	Lumens efficiency: 100Lm	3800-5000K, 5800 Lm
	Beam angle: 100°120°/150°85°/155°80°	Material: Aluminum	
	Input voltage: AC100-240V (HLG-60W)		5000-7000k, 6300 Lm
60w tunnel			
	Power consupction: 90Watt	IP65	2500k-3700k,8000 Lm
	LED type: high power	LED chip: 72pcs CREE XTE	
	Power efficiency: >85%	Lumens efficiency: 100Lm	3800-5000K, 8800 Lm
	Beam angle: 100°120°/150°85°/155°80°	Material: Aluminum	
	Input voltage: AC100-240V (HLG-100W)		5000-7000k, 10600 Lm
90w tunnel			
	Power consupction: 120Watt	IP65	2500k-3700k,10000 Lm
	LED type: high power	LED chip: 72pcs CREE XTE	
	Power efficiency: >85%	Lumens efficiency: 100Lm	3800-5000K, 11000 Lm
	Beam angle: 100°120°/150°85°/155°80°	Material: Aluminum	
	Input voltage: AC85-265V (HLG-120W)		5000-7000k, 13200 Lm
120w tunnel – 1			
	Power consupction: 120Watt	IP65	2500k-3700k,11000 Lm
	LED type: high power	LED chip: 96pcs CREE XTE	
	Power efficiency: >85%	Lumens efficiency: 100Lm	3800-5000K, 11800 Lm
	Beam angle: 100°120°/150°85°/155°80°	Material: Aluminum	
	Input voltage: AC85-265V (HLG-120W)		5000-7000k, 14200 Lm
120w tunnel			
	Power consupction: 150Watt	IP65	2500k-3700k,13700 Lm
	LED type: high power	LED chip: 96pcs CREE XTE	
	Power efficiency: >85%	Lumens efficiency: 100Lm	3800-5000K, 14700 Lm
	Beam angle: 100°120°/150°85°/155°80°	Material: Aluminum	
	Input voltage: AC85-265V (HLG-150W)		5000-7000k, 17600 Lm
150w tunnel			

Australian Lighting Solutions

	Power consuption: 200Watt	IP65	2500k-3700k,18300 Lm
	LED type: high power	LED chip: 96pcs CREE XTE	
	Power efficiency: >85%	Lumens efficiency: 100Lm	3800-5000K, 19600 Lm
	Beam angle: 100*120°/150*85°/155*80°	Material: Aluminum	
	Input voltage: AC85-265V (HLG-240W)		5000-7000k, 23600 Lm
	Power consuption: 180Watt	IP65	2500k-3700k,17000 Lm
	LED type: high power	LED chip: 144pcs CREE XTE	
	Power efficiency: >85%	Lumens efficiency: 100Lm	3800-5000K, 17800 Lm
	Beam angle: 100*120°/150*85°/155*80°	Material: Aluminum	
	Input voltage: AC85-265V (HLG-240W)		5000-7000k, 18500 Lm
	Power consuption: 240Watt	IP65	2500k-3700k,17000 Lm
	LED type: high power	LED chip: 144pcs CREE XTE	
	Power efficiency: >85%	Lumens efficiency: 100Lm	3800-5000K, 17800 Lm
	Beam angle: 100*120°/150*85°/155*80°	Material: Aluminum	
	Input voltage: AC85-265V (HLG-240W)		5000-7000k, 18500 Lm
	Power consuption: 280Watt	IP65	2500k-3700k,25620 Lm
	LED type: high power	LED chip: 144pcs CREE XTE	
	Power efficiency: >85%	Lumens efficiency: 100Lm	3800-5000K, 27500 Lm
	Beam angle: 100*120°/150*85°/155*80°	Material: Aluminum	
	Input voltage: AC85-265V (HLG-320W)		5000-7000k, 32800 Lm